

668N
Click-type torque bars, for right-hand and left-hand tightening, torque accuracy: $\pm 3\%$
UNI EN ISO 6789

- scale increased by 60% for improved visibility and setting accuracy
- torque adjusting speed increased by 40%
- handle and lens materials resistant to all chemical substances used in automotive sector, industry and aviation
- red colour of o-ring indicates that wrench is unlocked and torque can be adjusted
- when not in use, set torque to lowest value of torque wrench range
- recalibration reminder shows time to recalibrate wrench (4 steps: 3, 6, 9 and 12 months)



| art. | Nm | Kgfm | lbf.ft | \varnothing mm | L mm | LB mm | LS mm | \bar{m} g |
|-----------|--------|---------|--------|---------------------|---------|----------|----------|----------------|
| 006680002 | 5÷25 | 0,5÷2,5 | 4÷18 | 16 | 220 | 148 | 32 | 300 |
| 006680005 | 10÷50 | 1÷5 | 7÷37 | 16 | 307 | 229 | 32 | 590 |
| 006680010 | 20÷100 | 2÷10 | 15÷75 | 16 | 376 | 269 | 32 | 670 |
| 006680020 | 40÷200 | 4÷20 | 30÷150 | 16 | 450 | 352,6 | 32 | 795 |
| 006680030 | 60÷300 | 6÷30 | 50÷220 | 16 | 588 | 475,9 | 32 | 1230 |