

NF E 74.303

- Special heat treatment for increased surface hardness.
- They stand out from double ended hexagon/bi-hex socket wrenches item 937 for glossy surface finish, obtained from mechanical and manual working processes.
- Can be used with sliding handle in through hole.
- Hole on short side allows access to nut, e.g. with projecting threads.



art.	mm	Ø mm	L mm	Ø1 mm	A mm	A1 mm	L1 mm	g
009320006	6x6	11,5	110	5,0	8,0	15,0	15,0	55
009320007	7x7	12,5	116	6,0	9,0	18,0	15,0	60
009320008	8x8	13,0	120	6,0	11,0	20,0	21,0	65
009320009	9x9	14,0	125	7,0	11,0	20,0	21,0	75
009320010	10x10	16,5	133	8,0	13,0	22,0	25,0	105
009320011	11x11	17,5	143	8,5	14,0	23,0	25,0	125
009320012	12x12	19,0	148	8,5	14,0	25,0	25,0	165
009320013	13x13	19,5	154	9,5	16,0	28,0	34,0	175
009320014	14x14	21,5	167	10,0	17,0	28,0	34,0	220
009320015	15x15	22,5	182	10,0	17,0	29,0	40,0	235
009320016	16x16	24,5	193	11,0	20,0	33,0	40,0	335
009320017	17x17	26,0	198	12,0	20,0	34,0	44,0	340
009320018	18x18	26,5	215	13,0	20,0	34,0	44,0	370
009320019	19x19	29,0	220	14,0	22,0	35,0	48,0	435
009320020	20x20	30,5	222	14,0	22,0	37,0	48,0	485
009320021	21x21	30,5	236	16,0	25,0	39,0	48,0	575
009320022	22x22	32,5	250	16,0	25,0	41,0	52,0	610
009320023	23x23	33,5	256	17,0	26,0	44,0	52,0	705
009320024	24x24	35,0	272	19,0	27,0	46,0	55,0	805
009320025	25x25	36,5	282	19,0	27,0	47,0	55,0	895
009320026	26x26	37,5	296	20,0	28,0	47,0	61,0	950
009320027	27x27	39,0	296	21,0	28,0	50,0	61,0	1220
009320028	28x28	39,0	314	22,0	28,0	51,0	61,0	1235
009320030	30x30	42,5	348	23,0	31,0	51,0	70,0	1520
009320032	32x32	45,5	364	24,0	32,0	51,0	70,0	1800

