

NF E 74.303

- Special heat treatment for increased surface hardness.
- They stand out from double ended hexagon/bi-hex socket wrenches item 937 for glossy surface finish, obtained from mechanical and manual working processes.
- Can be used with sliding handle in through hole.
- Hole on short side allows access to nut, e.g. with projecting threads.



art.	mm	Ø mm	L mm	Ø1 mm	A mm	A1 mm	L1 mm	g
009330006	6x6	11,5	110	5,0	8,0	15,0	15,0	55
009330007	7x7	12,5	116	6,0	9,0	18,0	15,0	60
009330008	8x8	13,0	120	6,0	11,0	20,0	21,0	65
009330009	9x9	14,0	125	7,0	11,0	20,0	21,0	75
009330010	10x10	16,5	133	8,0	13,0	22,0	25,0	105
009330011	11x11	17,5	143	8,5	14,0	23,0	25,0	125
009330012	12x12	19,0	148	8,5	14,0	25,0	25,0	165
009330013	13x13	19,5	154	9,5	16,0	28,0	34,0	175
009330014	14x14	21,5	167	10,0	17,0	28,0	34,0	220
009330015	15x15	22,5	182	10,0	17,0	29,0	40,0	235
009330016	16x16	24,5	193	11,0	20,0	33,0	40,0	335
009330017	17x17	26,0	198	12,0	20,0	34,0	44,0	340
009330018	18x18	26,5	215	13,0	20,0	34,0	44,0	370
009330019	19x19	29,0	220	14,0	22,0	35,0	48,0	435
009330020	20x20	30,5	222	14,0	22,0	37,0	48,0	485
009330021	21x21	30,5	236	16,0	25,0	39,0	48,0	575
009330022	22x22	32,5	250	16,0	25,0	41,0	52,0	610
009330023	23x23	33,5	256	17,0	26,0	44,0	52,0	705
009330024	24x24	35,0	272	19,0	27,0	46,0	55,0	805
009330025	25x25	36,5	282	19,0	27,0	47,0	55,0	895
009330026	26x26	37,5	296	20,0	28,0	47,0	61,0	950
009330027	27x27	39,0	296	21,0	28,0	50,0	61,0	1220
009330028	28x28	39,0	314	22,0	28,0	51,0	61,0	1235
009330030	30x30	42,5	348	23,0	31,0	51,0	70,0	1520
009330032	32x32	45,5	364	24,0	32,0	51,0	70,0	1800

