





ISO 2936

- Flat, chamfered ends for optimal screw fit.

|  | art. | mm | L | L1 |  g |
|---|--------|-----|-----|-----|---|
| 000960013 | 96 0,9 | 0,9 | 35 | 8 | 0,6 |
| 000960014 | 96 1,3 | 1,3 | 39 | 10 | 0,8 |
| 000960015 | 96 1,5 | 1,5 | 45 | 15 | 0,9 |
| 000960020 | 96 2 | 2 | 50 | 17 | 1,8 |
| 000960025 | 96 2,5 | 2,5 | 57 | 20 | 3 |
| 000960030 | 96 3 | 3 | 64 | 22 | 4,9 |
| 000960035 | 96 3,5 | 3,5 | 68 | 25 | 7,2 |
| 000960040 | 96 4 | 4 | 72 | 28 | 10 |
| 000960045 | 96 4,5 | 4,5 | 78 | 30 | 13,6 |
| 000960050 | 96 5 | 5 | 83 | 32 | 17,8 |
| 000960055 | 96 5,5 | 5,5 | 88 | 35 | 20 |
| 000960060 | 96 6 | 6 | 94 | 37 | 29 |
| 000960070 | 96 7 | 7 | 99 | 40 | 41,9 |
| 000960080 | 96 8 | 8 | 105 | 43 | 58,2 |
| 000960090 | 96 9 | 9 | 111 | 46 | 78 |
| 000960100 | 96 10 | 10 | 119 | 49 | 101,4 |
| 000960110 | 96 11 | 11 | 126 | 52 | 128,2 |
| 000960120 | 96 12 | 12 | 134 | 56 | 160,1 |
| 000960130 | 96 13 | 13 | 142 | 62 | 205 |
| 000960140 | 96 14 | 14 | 151 | 69 | 252 |
| 000960160 | 96 16 | 16 | 165 | 75 | 367,2 |
| 000960170 | 96 17 | 17 | 174 | 79 | 428 |
| 000960190 | 96 19 | 19 | 196 | 88 | 609,6 |
| 000960220 | 96 22 | 22 | 216 | 100 | 910 |
| 000960240 | 96 24 | 24 | 242 | 112 | 1192 |
| 000960270 | 96 27 | 27 | 271 | 125 | 1708 |
| 000960300 | 96 30 | 30 | 309 | 140 | 2467 |
| 000960312 | 96 32 | 32 | 341 | 155 | 3038 |
| 000960316 | 96 36 | 36 | 385 | 174 | 4316 |

